

LISTADO DE PRODUCTOS INPROCIL PARA DIÓXIDO DE CARBONO - NORMA IRAM 2533

MODELO	DIAMETRO (mm)	CAPACIDAD (m ³)	CAPACIDAD (Lts.)	LONGITUD (mm)	PESO (Kg)	PRESION DE PRUEBA	PRESION DE TRABAJO	ROSCA DE PICO	TORQUE SUGERIDO	NORMA
IP.GC.114.003.150	114,3	0,5	3,3	455	7,7	250	150	BSPT 1/2"	18 Kn.m	IRAM 2533
IP.GC.140.003.150	139,7	0,5	3,3	364	9	250	150	IRAM-2539 Ø3/4"	25 Kn.m	IRAM 2533
IP.GC.140.007.150	139,7	1	6,6	602	13					
IP.GC.140.010.150	139,7	1,5	10	878	19					
IP.GC.140.013.150	139,7	2	13,3	1170	23					
IP.GC.140.015.150	139,7	2,25	15	1245	24,5					
IP.GC.232.020.150	232,0	4	20	680	28	250	150	IRAM-2539 Ø3/4"	25 Kn.m	IRAM 2533
IP.GC.232.025.150	232,0	5	25	800	31					
IP.GC.232.030.150	232,0	6	30	920	35					
IP.GC.232.035.150	232,0	7	35	1045	39					
IP.GC.232.040.150	232,0	8	40	1180	43					
IP.GC.232.045.150	232,0	9	45	1300	47					
IP.GC.232.050.150	232,0	10	50	1420	51					
IP.GC.244.030.150	244,5	6	30	890	40	250	150	IRAM-2539 Ø3/4"	25 Kn.m	IRAM 2533
IP.GC.244.040.150	244,5	8	40	1100	48					



Gris
CO2

Rojo
Extintores



CERTIFICACIONES



Management
System
ISO 9001:2015

www.tuv.com
ID 9000019896

